

## Especificaciones técnicas por medidas

### Serie BS18

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
8.25R16LT	6.50	16PR	126/122	K	13	1800/1600	770/770
10.00R20	7.50	18PR	149/146	K	16	3250/3000	930/930
11.00R20	8.00	18PR	152/149	G	16.5	3550/3250	930/930
12.00R20	8.50	18PR	154/151	K	17	3790/3270	840/770

### Serie BS28

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
7.50R16LT	6.00	14PR	122/118	K	12	1495/1310	740/740
8.25R16LT	6.50	16PR	128/124	K	13	1800/1600	770/770
9.00R20	7.00	16PR	144/142	K	15.5	2800/2650	900/900
10.00R20	7.50	18PR	149/146	K	16.5	3250/3000	930/930
11.00R20	8.00	18PR	152/149	J	17	3550/3250	930/930
12.00R20	8.50	18PR	154/149	J	17.5	3790/3270	840/770

### Serie BS29

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
9.00R20	7.00	16PR	144/142	J	17.5	2800/2650	900/900
10.00R20	7.50	18PR	149/146	K	18.5	3250/3000	930/930
11.00R20	8.00	18PR	152/149	J	19.5	3550/3250	930/930
12.00R20	8.50	18PR	154/149	J	20.5	3790/3270	840/770

## Especificaciones técnicas por medidas

### Serie BY06

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
10.00R20	7.50	18PR	149/142	K	24.5	3000/2630	930/930
11.00R20	8.00	18PR	152/149	G	24.5	3550/3250	930/930
12.00R20	8.50	18PR	154/149	G	24.5	3790/3270	840/770
12.00R20	8.50	20PR	153/153	G	24.5	4000/3650	900/900

### Serie BY08

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
10.00R20	7.50	18PR	149/142	L	17.5	3250/3000	930/930
11.00R20	8.00	18PR	152/149	K	18.5	3550/3250	930/930
12.00R20	8.50	18PR	154/149	K	20	3790/3270	840/770

### Serie BY25

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
11.00R20	8.00	18PR	152/149	J	20	3550/3250	930/930
12.00R20	8.50	18PR	154/149	J	20.5	3790/3270	840/770
12.00R20	8.50	20PR	156/153	G	20.5	4000/3650	900/900

## Especificaciones técnicas por medidas

### Serie BY26

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
9.00R20	7.00	16PR	144/142		17.5	2800/2650	900/900
11.00R20	8.00	18PR	152/149	J	17.5	3550/3250	930/930
12.00R20	8.50	20PR	156/153	G	17.5	4000/3650	900/990

### Serie BY35

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
10.00R20	7.50	18PR	149/142	L	17.5	3250/3000	930/930
11.00R20	8.00	18PR	152/149	J	20	3550/3250	930/930
12.00R20	8.50	18PR	154/149	J	20.5	3790/3270	840/770

### Serie BY55

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
10.00R20	7.50	18PR	149/142	L	17.5	3250/3000	930/930
11.00R20	8.00	18PR	152/149	K	20	3550/3250	930/930
12.00R20	8.50	18PR	154/149	K	20.5	3790/3270	840/770

# Especificaciones técnicas por medidas

## Serie BYS98

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
11R22.5	8.25	18PR	148/145	M	17	3150/2900	850/850
12R22.5	8.25	18PR	152/148	M	17	3550/3150	850/850
295/80R22.5	9.00	18PR	152/148	M	17	3550/3150	850/850
315/80R22.5	9.00	20PR	161/154	G	17	4625/3750	900/900

## Serie BYD68

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
11R22.5	8.25	18PR	148/145	M	18.5	3150/2900	850/850
12R22.5	8.25	18PR	152/148	M	18.5	3550/3150	850/850
295/80R22.5	9.00	18PR	152/148	M	18.5	3550/3150	850/850
315/80R22.5	9.00	20PR	161/154	G	18.5	4625/3750	900/900

## Serie BY88

SIZE	ESTÁNDAR RIM	PLY RATING	LOAD INDEX (SINGLE/DUAL)	SPEED RATE	TREAD DEPTH (mm)	MAX LOAD (kg) (Single/Dual)	pressure (KPA) (SINGLE/DUAL)
12R22.5	9.00	18PR	152/148	K	18	3550/3150	850/850